
Fiberglass Flooring Tissue

PRODUCT DESCRIPTION

Fiberglass flooring tissue is produced from fiberglass chopped strands by wet lay out process. The features of this product is even surface and fast impregnation of melted PVC. Using the fiberglass flooring tissue as stabilizing layer, the PVC floor become more even and flat,obviously minimized the problem of deforming and bubble of the traditional PVC floor without fiberglass layer. The PVC floor made by this product have the property of good stability, smooth appearance, bright color, and convenient mounting. The PVC floor is widely used decoration materials for hospitals, schools, libraries, air port and other public places.











CHARACTERISTICS

- Fiber Uniformly Dispersed
- Smooth Surface, Less Wool Yarn
- Easy to Coating PVC
- Stiff, Folding Resistance, not Easy to deformation
- Good Dimensional Stability

TECHNICAL DATA

Product code	Unit Weight	LOI	MD Tensile Strength	CD Tensile Strength	Thickness	Moisture Content
	g/m2	**%**	N/5CM	N/5CM	mm	**%**
F-DB25	25	≤25	≥ 80	≥50	0.2	≤ 1.0
F-DB0.3	35	≤30	≥ 150	≥70	0.30	≤ 1.0
F-DB40	40	≤30	≥180	≥80	0.35	≤ 1.0
F-DB45	45	≤30	≥ 200	≥90	0.35	≤ 1.0
F-DB50	50	≤30	≥250	≥100	0.40	≤ 1.0
Testing Basis	ISO3374	ISO1887	ISO3342	ISO4603	ISO 3344	ISO 3344
Paper core diameter: 152mm						

Remark: 1. Other specification can be customized according to customer' s demand.

2. The technical data above is for reference only

PACKING

Every roll in plastic film without pallet.

STORAGE

This product should be stored in a dry, ventilated, and rainproof place, with temperatures from 5 ° Cto 35 ° C and humidity between 35% and 65%. It is recommended to be kept in the intact package when not used to avoid damp.

Address: No.20 Jiangjun Ave., Nanjing, P.R. China
URL: www. njefg.com
E-mail: sales@njefg.com
Fax: +86 25 58321442
Tel: +86 25 52270147
Mobile : 0086 18851651909 (WhatsApp)